



- Certifications**
- Conforms to ANSI/BHMA A156.13, Series 1000, Grade 1
 - cULus listed, 3hr fire-rating
 - UL10C Positive Pressure Rated
 - Levers meet ADA (ANSI 117.1) requirements
 - 5 Year limited warranty

- Door Thickness**
- 1¾" (44.5 mm)
 - 2–2¼" (51–57 mm) – available

- Handing**
- Handed, field reversible

- Backset**
- 2¾" (70 mm)

- Spring Latch**
- Brass, 2 piece anti-friction
 - ¾" (19 mm) throw

- Deadbolt**
- Solid bolt, 2 security pins
 - 1" (25.4 mm) throw

- Faceplate**
- 1¼ x 8" (32 x 203 mm), square corners
 - Adjusts for bevelled doors up to ⅛" (3 mm)

- Strike**
- ASA T-type strike and dust-box

- Cylinder**
- 6 pin mortise cylinder
 - Schlage "C" with 2 keys
 - Small format interchangeable core (SFIC) mortise housing available (SFIC not included)
 - Other keyways and keying options available, including CX5 high security*

- Sectional Trim**
- Brass lever or knob
 - Brass rose
 - S–Round: $\varnothing 2\frac{7}{16} \times \frac{1}{2}$ " (61.5 x 12.7 mm)
 - SQ–Square: $1\frac{7}{8} \times 1\frac{7}{8} \times \frac{1}{2}$ " (48 x 48 x 12.7 mm)

- Escutcheon Trim**
- Brass lever or knob
 - Brass escutcheon
 - E–Regular $2 \times 8\frac{1}{16} \times \frac{1}{2}$ " (50 x 205 x 12.7 mm)
 - E2–Wide $2\frac{1}{2} \times 8\frac{1}{4} \times \frac{1}{2}$ " (63 x 210 x 12.7 mm)
 - E3–Large $2\frac{3}{4} \times 10\frac{3}{4} \times \frac{1}{2}$ " (70 x 273 x 12.7 mm)

- Chassis**
- Rose trim: concealed mounting screws
 - Thumb-turn: exposed mounting screws
 - Escutcheon: exposed mounting screws
 - Single action egress

- Functions**
- | | |
|------------------------|--------------------------|
| 10 Passage | 80 Storeroom |
| 42 Privacy | 84 Storeroom w/ deadbolt |
| 42I Privacy, indicator | 171 Dummy, single |
| 45 Entry | 172 Dummy, back-to-back |
| 50 Office | |
| 56 Dormitory | |
| 70 Classroom | |

- Lever Styles** A–Apollo, R–Circa, C–Cornell, D–Dartmouth, G–Glasgow, L–Linea, S–Stanford, F–The Flat, XT–Intersect

- Knob Styles** K–Kent

- Finish** 15–Satin nickel, 19–Matte black, 26D–Satin chrome
Other finishes available by special order

DM	45	L	–	SQ	F	26D
SERIES	FUNCTION	HAND ¹		TRIM	STYLE	FINISH

(1) L–LEFT R–RIGHT

SELECTION GUIDE


SERIES	TRIM	STYLE**	FUNCTION ¹	FINISH ¹	/CASE
DM	S, SQ, E, E2, E3	ALL	10 Passage	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	42 Privacy	15, 19, 26D	6
DM	E	ALL	42I Privacy indicator ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	45 Entry ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	50 Office ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	56 Dormitory ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	70 Classroom ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	80* Storeroom ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	84* Storeroom, with deadbolt ➡	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	171 Dummy, single	15, 19, 26D	6
DM	S, SQ, E, E2, E3	ALL	172 Dummy, back-to-back	15, 19, 26D	6

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED – PLEASE CONTACT


➡ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE – PLEASE CONTACT (*) ONE-SIDED INSTALLATION MODEL AVAILABLE (**) XT / INTERSECT NOT AVAILABLE WITH ESCUTCHEON

LEVERS & KNOBS


A–Apollo




C–Cornell




D–Dartmouth




F–The Flat




G–Glasgow




L–Linea




R–Circa




S–Stanford



XT–Intersect



K–Kent



STYLE	A	B	C ¹
A–Apollo*	3 ¹ / ₁₆ (78)	4 ⁵ / ₈ (116)	2 ¹ / ₁₆ (53)
C–Cornell	2 ⁷ / ₈ (73)	5 ⁵ / ₁₆ (134)	⁵ / ₈ (16)
D–Dartmouth	2 ⁷ / ₁₆ (61.5)	5 ⁷ / ₈ (149)	1 ¹ / ₁₆ (17)
F–The Flat	2 ⁷ / ₈ (73)	5 ¹ / ₂ (139.7)	2 ³ / ₁₆ (55.5)
G–Glasgow	2 ⁷ / ₈ (73)	5 ¹ / ₁₆ (128)	2 ¹ / ₁₆ (52)

IN (MM) (1) ALL ROSES AND ESCUTCHEONS ARE 12.7 (1/2) THICK


STYLE	A	B	C ¹
L–Linea	2 ¹³ / ₁₆ (71.4)	5 (127)	1 ¹⁵ / ₁₆ (48.4)
R–Circa	2 ⁹ / ₁₆ (65.5)	5 ¹ / ₂ (139.7)	1 ⁷ / ₈ (47)
S–Stanford	2 ⁹ / ₁₆ (65.5)	5 ¹ / ₁₆ (128)	⁹ / ₁₆ (14)
XT–Intersect*,**	2 ¹⁹ / ₆₄ (56)	4 ¹⁵ / ₁₆ (125)	¹ / ₂ (12.7)
K–Kent	2 ⁷ / ₁₆ (61.5)	ø 2 (50.8)	—

(*) HANDED LEVER, NOT FIELD REVERSIBLE,

(**) SECTIONAL ONLY, NOT AVAILABLE WITH ESCUTCHEON




LOCK TRIMS



TRIM	E ¹	E2	E3 ²	S	SQ
Description	Regular escutcheon	Wide escutcheon	Large escutcheon	Round rose	Square rose
Width (W)	2 (50)	2 1/2 (64)	2 3/4 (70)	ø 2 3/8 (60)	1 7/8 (48)
Height (H)	8 1/16 (205)	8 1/4 (210)	10 3/4 (273)	—	1 7/8 (48)
Depth (D)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)
Material	Brass	Brass	Brass	Brass	Brass

IN (MM) (1) AVAILABLE WITH PRIVACY INDICATOR—42I (2) OPTIONAL ENGRAVING AVAILABLE—PLEASE CONTACT

DIMENSIONS



MUST BE INSTALLED ON A DOOR WITH A SOLID LOCK STILE WIDTH OF AT LEAST 5" (127 MM) OR WITH APPROPRIATE REINFORCEMENT.

PARTS & ACCESSORIES



DM45X-PS

Replacement strike for 1 3/4 (45) thick door.
(Functions 42, 45, 56, 84)



DM80X-PS

Replacement strike for 1 3/4 (45) thick door.
(Functions 10, 50, 70, 80)



DM45X-PE

Mortise lock emergency privacy key; round.
Includes plate and screws.



DM45X-PES

Mortise lock emergency privacy key; square.
Includes plate and screws.



DM45X-PT

Mortise lock thumbturn; round.



DM45X-PTS

Mortise lock thumbturn; square.



DM00X-PPRVI

Privacy indicator kit, round. Includes replacement interior/exterior trims for 42 function. 1 3/4 (44.5) door thickness only.



DM00X-PPRVIQ

Privacy indicator kit, square. Includes replacement interior/exterior trims for 42 function. 1 3/4 (44.5) door thickness only.



DM00X-PPRVI-ECYL

Privacy indicator kit, round. Includes replacement interior/exterior trims for 45, 56 or 84 function. 1 3/4 (44.5) door thickness only. Includes DM00X-PECYL cylinder and 2 keys.



DM00X-PPRVIQ-ECYL

Privacy indicator kit, square. Includes replacement interior/exterior trims for 45, 56 or 84 function. 1 3/4 (44.5) door thickness only. Includes DM00X-PECYL cylinder and 2 keys.



DM45X-PR

Mortise cylinder collar with spring; round.
Ø 1 11/16 x 3/8 (Ø 43 x 9)



DM45X-PRS

Mortise cylinder collar with spring; square.
1 7/8 x 1 7/8 x 3/8 (48 x 48 x 9)



DM00X-PSCYL

- 1 1/8 (28.6) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys
- For sectional installations on 1 3/4 (45) thick doors
- Includes DM00X-PCAM

DM00X-PECYL

- 1 1/4 (31.8) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys
- For escutcheon installations on 1 3/4 (45) thick doors
- Includes DM00X-PCAM



DM00X-PCAM

Replacement mortise cylinder cam, with screws



DM00X-PKDT225

Installation kit for 2-2 1/4 (51-57) thick doors.

- Includes extended thumb-turn, spindle, springs, strike and mounting hardware for rose or escutcheon trim
 - Mortise cylinder NOT INCLUDED
- Please contact for details*

