



ASSA ABLOY

ELECTRIFIED CLOSERS AND HOLDERS

TABLE OF CONTENTS

| 7100SZ | |
|---|-------|
| Introduction, Features, Benefits, Certifications, Patents | 3 |
| Specifications | 4 |
| 7110SZ, 7150SZ | 5 |
| 7120SZ, 7130SZ | 6 |
| Parts List | 7 |
| How To Order | 8 |
| 7200 | |
| Introduction, Features | c |
| Overview, Certifications, Specifications | |
| Explanation of Features | |
| 7210MPSO, 7210RFS, 7250MPSO | |
| 7220MPSO, 7220RF, 7230MPSO, 7230RFS | |
| 7240 | |
| 7290 | |
| Parts List | |
| How To Order | |
| 7700PT | |
| Introduction, Features, Overview, Certifications | 18 |
| Explanation of Features, Voltage Info. | |
| 7705PTO | |
| P7705PTO | |
| Electrical Info., Specifications | |
| Parts List | |
| How To Order | |
| | |
| Smok-Chek® V, Smok-Chek VI®, Checkmate® 99 | 20 |
| Introduction, General Info, Specifications | 26 |
| Smok-Chek V | |
| 0600, 0601 | |
| 0602, 0100 | |
| 0101 | |
| How To Order | |
| Parts List | 31-32 |
| Smok-Chek VI | 22 |
| 4 Pull, 4 Push | |
| How To Order, Product Comparison Chart | |
| Parts List | 35-36 |
| Checkmate 99 99-726, 99-926 | 27 |
| How To Order, Product Comparison Chart | |
| Parts List | 2.0 |
| 1 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | |

7100SZ Series 7200 Series 7700PT Series Smok-Chek V Smok-Chek VI Checkmate



7100SZ SAFEZONE® ELECTRIFIED CLOSERS AND HOLDERS



INTRODUCTION

The 7100 Series SafeZone® door closer safeguards occupants throughout a variety of facilities with the detection of movement through doorways and intelligent door control functions. A multi-point electromechanical closer with a programmable motion sensor allows the door to open manually and remain open when one or more people travel through the opening.



FEATURES

- Multi-point, electromechanical closer/holder
- Sensor detects movement in both directions
- Selectable hold open time and sensitivity
- Push or pull side mounting
- Handed units
- Spring sizes 3, 4 or 5 (models 7110SZ and 7150SZ);
 Spring sizes 2, 3, 4 or 5 (models 7120SZ and 7130SZ)
- Fail safe operation
- Optional dual sensor
- 2-year limited warranty

BENEFITS

- Energy savings realized by power engaging only when motion is detected
- Extends door life and minimizes wear and tear on hardware by limiting unnecessary cycles

CERTIFICATIONS

- Certified to meet ANSI/BHMA A 156.15 Release Devices BHMA
- UL / cUL listed for use on fire rated doors (1)
- UL10C listed for positive pressure fire test
- The following models comply with requirements for the Americans with Disabilities Act (A.D.A) and ANSI standard A 117.1
 - Push Side: 7122SZ, 7132SZ
 - Pull Side: 7113SZ, 7153SZ
- This product is manufactured in an ISO 9001 facility
- UL certified environmental product declaration

PATENT

Patent Pending